



Item 79STRAW

SAFETY DATA SHEET

Issuing date 13-Jun-2023

Revision Date 13-Jun-2023

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/REPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier
Product name

#79 STRAW RUST PENETRANT

Other means of identification

Product code

F04S61

Product Type
Synonyms

Extremely Flammable Aerosol
None

Recommended use of the chemical and restrictions on use

Recommended Use

Rust Penetrant

Uses advised against

No information available

Manufactured For:
1st Ayd Corporation
1325 Gateway Drive
Eggin, IL 60124
PHONE: 1-800-422-3033
MON-FRI, 8AM-5PM

Emergency telephone number

Chemical Emergency Phone Number CHEMTREC: 1-800-262-8200 ID
1195 (UNITED STATES)
INTERNATIONAL 1-703-741-5500

2. HAZARDS IDENTIFICATION**Classification**

This product is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).
Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Aspiration hazard	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Label elements**Danger****Emergency Overview****Hazard statements**

Harmful if inhaled
Causes skin irritation
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Appearance Slightly Hazy

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Avoid breathing dust, fume, gas, mist, vapors, spray.
Use only outdoors or in a well-ventilated area.
Wash face, hands and any exposed skin thoroughly after handling.
Wear protective gloves.
Keep away from heat, sparks, open flames, hot surfaces. No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container. Do not pierce or burn, even after use.

Precautionary Statements - Response

Specific treatment (see first aid on this label).
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor, physician if you feel unwell.
IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up
Protect from sunlight. Store in a well-ventilated place
Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)
Not applicable

Other information

0 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Distillates (petroleum), hydrotreated Light	64742-47-8	20-30
PROPANE/SOBUTANE/BUTANE	68476-86-8	20-30
NAPHTHENE OIL, SEVERELY HYDROTREATED	64742-52-5	10-20
KEROSENE	8008-20-6	10-20
PETROLEUM DISTILLATES	64742-47-8	10-20
2-BUTOXYETHANOL	111-76-2	1-10
NaphthalenesulfonicAcid/ CaSalt	57855-77-3	1-10
ETHYLENE GLYCOL	107-21-1	<0.1
NAPHTHALENE	91-20-3	<0.1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures****General advice**

Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.

Eye contact

Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.

Skin contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.

Inhalation

Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.

Ingestion

Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms and effects, both acute and delayed

Main Symptoms

Harmful if inhaled. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**Water fog/Dry chemical, Foam, Carbon dioxide (CO₂). Cool container/tanks with water spray.**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.**Specific hazards arising from the chemical**

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data**Sensitivity to Mechanical Impact** none**Sensitivity to Static Discharge** Yes.**Protective Equipment and Precautions for Firefighters**

In the event of fire and/or explosion do not breathe fumes. As in any fire, wear self-contained breathing apparatus pressure-demand, MSH/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Use with adequate ventilation to keep the exposure levels below the OELs.

Environmental precautions**Environmental precautions**

Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Report spills as required by local and federal regulations.

Methods and material for containment and cleaning up**Methods for Containment**

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up

Absorb with sand, clay, or other suitable material. Hard surfaces may be mopped with water. Dam up. Cover liquid spill with sand, earth, or other noncombustible absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE**Precautions for safe handling****Advice on safe handling**

Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products

Strong acids, alkali, or oxidizing agents.

Aerosol Level

3

8. EXPOSURE CONTROL/PERSONAL PROTECTION**Control Parameters****Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Distillates (petroleum), hydrocracked Light 64742-47-8	TWA: 200 PPM 8 hours		
PROPANE/ISOBUTANE-BUTANE 68476-86-8	74-99-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-99-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-99-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1300 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³
KEROSENE 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures		TWA: 100 mg/m ³
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
ETHYLENE GLYCOL 107-21-1	STEL: 50 ppm vapor fraction STEL: 10 mg/m ³ inhalable particulate matter, aerosol only TWA: 25 ppm vapor fraction	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³ S*	
NAPHTHALENE 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 982 (11th Cir., 1992).

Appropriate engineering controls**Engineering Measures**

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Aerosol	Odor	Solvent
Appearance	Slightly Hazy	Odor Threshold	
Color	Amber		
Property	Values	Remarks - Method	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash Point	-96.4 °C / -141 °F	Based on propellant	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air	No information available		
upper flammability limit			
lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific gravity	0.785		
Water solubility	Practically insoluble		
Partition coefficient: n-octanol/water			
Autoignition temperature	No information available	Not applicable	
Hyphen	No information available		
Viscosity	No information available		
Explosive properties			

Other information

VOC Content(%)

49.64

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks.

Incompatible materials

Strong acids, alkali, or oxidizing agents.

Hazardous decomposition products

Carbon oxides, Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product information

Inhalation

Harmful if inhaled. Avoid inhaling vapors or mists. May cause respiratory irritation, drowsiness or dizziness.

Eye contact

May be irritating to the eyes.

Skin contact

Causes skin irritation.

Ingestion

May be fatal if swallowed and enters airways.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Distillates (petroleum), hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
64742-47-8			
NAPHTHENE OIL, SEVERELY HYDROTREATED	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
64742-52-5			
KEROSENE	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
8008-20-6			
PETROLEUM DISTILLATES	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
64742-47-8			
2-BUTOXYETHANOL	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
111-76-2			
NaphthalenesulfonicAcid,CaSalt	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 466 ppm (Rat) 4 h
57855-77-3			> 18 mg/L (Rat) 1 h
ETHYLENE GLYCOL	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)	> 2.5 mg/L (Rat) 6 h
107-21-1			
NAPHTHALENE	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 0.4 mg/L (Rat) 4 h
91-20-3			

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Harmful if inhaled. Causes skin irritation. May cause eye and respiratory irritation. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation
Eye damage/irritation

Causes skin irritation.
May cause eye irritation.

Sensitization

Causes skin irritation. May cause eye and respiratory irritation.

Germ cell mutagenicity

No information available.

Carcinogenicity

Not a germ cell mutagen.
The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
KEROSENE	A3	Group 3	-	-
8008-20-6				
2-BUTOXYETHANOL	A3	Group 3	-	-
111-76-2				
NAPHTHALENE	A3	Group 2B	Reasonably Anticipated	X
91-20-3				

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Carcinogenic to Humans

Reproductive toxicity

This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic toxicity (single exposure)

No information available.

Specific target organ systemic

No information available.

toxicity (repeated exposure)

Chronic toxicity

Target organ effects

Aspiration hazard

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Eyes, Skin, Respiratory system, Central nervous system.
Harmful and may be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product information

Unknown acute toxicity
The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 3165 mg/kg
ATEmix (dermal) 12362 mg/kg
ATEmix (inhalation-gas) 198334 mg/l
ATEmix (inhalation-dust/mist) 16.9 mg/l
ATEmix (inhalation-vapor) 379 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Distillates (petroleum), hydrocracked light 64742-47-8	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncochymichus mykiss)	-	-
PROPANESOBUTANEN- BUTANE 68476-86-8	-	-	-	-
NAPHTHENIC OIL, SEVERELY HYDROTREATED 64742-52-5	-	LC50: >3000mg/L (96h, Oncochymichus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
PETROLEUM DISTILLATES 64742-47-8	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncochymichus mykiss) LC50: =1480mg/L (96h, Lepomis macrochirus) LC50: =2930mg/L (96h, Lepomis macrochirus)	-	EC50: >1000mg/L (48h, Daphnia magna)
2-BUTOXYETHANOL 111-76-2	-	LC50: =4100mg/L (96h, Oncochymichus mykiss) LC50: 14 - 18mg/L (96h, Oncochymichus mykiss) LC50: =27540mg/L (96h, Lepomis macrochirus) LC50: =40781mg/L (96h, Oncochymichus mykiss) LC50: 40000 - 60000mg/L (96h, Pimephales promelas) LC50: =16000mg/L (96h, Pocella reticulata)	-	EC50: =46300mg/L (48h, Daphnia magna)
ETHYLENE GLYCOL 107-21-1	EC50: 6500 - 13000mg/L (96h, Pseudokirchneriella salicophila)	-	-	EC50: =2.16mg/L (48h, Daphnia magna) EC50: =1.96mg/L (48h, Daphnia magna) EC50: 1.09 - 3.4mg/L (48h, Daphnia magna)
NAPHTHALENE 91-20-3	-	LC50: 5.74 - 6.44mg/L (96h, Pimephales promelas) LC50: =1.6mg/L (96h, Oncochymichus mykiss) LC50: 0.91 - 2.82mg/L (96h, Oncochymichus mykiss) LC50: =1.96mg/L (96h, Pimephales promelas) LC50: =31.0235mg/L (96h,	-	LC50: =2.16mg/L (48h, Daphnia magna) EC50: =1.96mg/L (48h, Daphnia magna) EC50: 1.09 - 3.4mg/L (48h, Daphnia magna)

	Lepomis macrochirus	
--	---------------------	--

Persistence and degradability

Bioaccumulation

Chemical name	Partition coefficient
PROPANE/SOBIANE-BUTANE 69476-96-8	2.8
2-BUTOXYETHANOL 111-76-2	0.81
ETHYLENE GLYCOL 107-21-1	-1.36
NAPHTHALENE 91-20-3	3.4

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Do not re-use empty containers. Empty containers may contain flammable or explosive vapors.

14. TRANSPORT INFORMATION

DOT Ground

LIMITED QUANTITY

IATA

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD. QTY

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	DSL/NDL	ENCS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
Distillates (petroleum), hydrofired Light	X	X	X	Not listed	X	X	X	X
PROPANE/SOBIANE	X	X	X	X	X	X	X	X
NEEN-BUTANE	X	X	X	X	X	X	X	X
NAPHTHENCOL, SEVERELY HYDROTREATED	X	X	X	Not listed	X	X	X	X

KEROSENE	X	X	X	X	X	X	X	X	X
PETROLEUM DISTILLATES	X	X	X	X	X	X	X	X	X
2-BUTOXYETHANOL	X	X	X	X	X	X	X	X	X
Naphthalenesulfonic acid, C ₁₀ H ₇ SO ₃	X	X	X	X	X	X	X	X	X
ETHYLENE GLYCOL	X	X	X	X	X	X	X	X	X
NAPHTHALENE	X	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 CHINA - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	111-76-2	1-10	1.0
ETHYLENE GLYCOL - 107-21-1	107-21-1	<0.1	1.0
NAPHTHALENE - 91-20-3	91-20-3	<0.1	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes
 Chronic health hazard Yes
 Fire hazard Yes
 Sudden release of pressure hazard Yes
 Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42). This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NAPHTHALENE 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
ETHYLENE GLYCOL 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
NAPHTHALENE 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical name	California Proposition 65
ETHYLENE GLYCOL - 107-21-1	Developmental (Ingested) <0.1%
NAPHTHALENE - 91-20-3	Cancer / <0.1%

Note: Ethylene Glycol CAS # 107-21-1 is considered a Proposition 65 chemical for developmental only when ingested. The purpose of this product is not for ingestion. NO warning for Ethylene Glycol is required for this product.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
KEROSENE 8008-20-6	X	X	X
2-BUTOXYETHANOL 111-78-2	X	X	X
ETHYLENE GLYCOL 107-21-1	X	X	X
NAPHTHALENE 91-20-3	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NEPA	Health hazards 2	Flammability 4	Instability 0	Special hazards -
HMS	Health hazards 2	Flammability 4	Physical hazards 1	Personal protection B

Prepared By

American Jetway Corporation

34136 Myrtle Street

Wayne, MI 48184-0126

13-Jun-2023

13-Jun-2023

Issuing date

Revision Date

Revision Note

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet