


1 Identification of the substance and manufacturer

Trade name: **FLAT BLACK**
 Product code: 0006201433
 Product category: PC9a Paints and coatings.
 Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 phone: 815-895-9101
 www.seymourpaint.com
 Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification**Classification of the substance or mixture**

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word**Hazard statements****Precautionary statements**

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes serious eye irritation.
 May cause respiratory irritation. May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a POISON CENTER/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Protect from sunlight. Store in a well-ventilated place.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients**Chemical characterization: Mixtures****Chemical Description:**

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	
74-98-6	propane	21.24%
1317-65-3	Calcium Carbonate	15.75%
106-97-8	n-butane	13.23%
110-19-0	Isobutyl Acetate	9.25%
64742-89-8	VM&P Naphtha	8.54%
108-65-6	PM acetate	4.54%
2807-30-9	Glycol Ether EP	4.19%
108-10-1	methyl isobutyl ketone	2.56%
107-87-9	Methyl Propyl Ketone	1.49%
112926-00-8	Silicon Dioxide	1.33%
		1.13%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
 Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

Trade name: FLAT BLACK

(Contd. of page 1)

5 Fire-fighting measures**Extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Can form explosive gas-air mixtures.**Special hazards:****Protective equipment for firefighters:**

A respiratory protective device may be necessary.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.**Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

7 Handling and storage**Precautions for safe handling**

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**PEL (USA) Long-term value: 2400 mg/m³, 1000 ppmREL (USA) Long-term value: 590 mg/m³, 250 ppmTLV (USA) Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
BEI**74-98-6 propane**PEL (USA) Long-term value: 1800 mg/m³, 1000 ppmREL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F in TLVs&BEIs book; NIC-EX

106-97-8 n-butaneREL (USA) Long-term value: 1900 mg/m³, 800 ppmTLV (USA) Short-term value: (2370) mg/m³, (1000) ppm
NIC-EX**110-19-0 Isobutyl Acetate**PEL (USA) Long-term value: 700 mg/m³, 150 ppmREL (USA) Long-term value: 700 mg/m³, 150 ppmTLV (USA) Short-term value: 172 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm**108-65-6 PM acetate**

WEEL (USA) Long-term value: 50 ppm

108-10-1 methyl isobutyl ketonePEL (USA) Long-term value: 410 mg/m³, 100 ppmREL (USA) Short-term value: 300 mg/m³, 75 ppmLong-term value: 205 mg/m³, 50 ppmTLV (USA) Short-term value: 307 mg/m³, 75 ppmLong-term value: 82 mg/m³, 20 ppm

BEI

107-87-9 Methyl Propyl KetonePEL (USA) Long-term value: 700 mg/m³, 200 ppmREL (USA) Long-term value: 530 mg/m³, 150 ppmTLV (USA) Short-term value: 529 mg/m³, 150 ppm**112926-00-8 Silicon Dioxide**PEL (USA) 20mppcf or 80mg/m³ /%SiO₂REL (USA) Long-term value: 6 mg/m³

See Pocket Guide App. C

TLV (USA) TLV withdrawn

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA) 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L

Medium: urine

Time: end of shift

Parameter: MIBK

Hygienic protection:Keep away from foodstuffs and animal feed. Wash hands after use.
Immediately remove all soiled and contaminated clothing.

(Contd. on page 3)

Trade name: FLAT BLACK

(Contd. of page 2)

Breathing equipment:

Wash hands after use.
 Avoid contact with the eyes and skin.
 Do not eat or drink while working.
 A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.

Eye protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.
 Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octanol/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content (less exempt solvents):	49.2 %
Solids content:	29.3 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

110-19-0 Isobutyl Acetate

Oral LD50 4763 mg/kg (rbt)

108-65-6 PM acetate

Oral LD50 8500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

108-10-1 methyl isobutyl ketone

Oral LD50 2100 mg/kg (rat)

Dermal LD50 16000 mg/kg (rab)

Inhalative LC50/4 h 8.3-16.6 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Other adverse effects:	No further relevant information available.

(Contd. on page 4)

Trade name: FLAT BLACK

(Contd. of page 3)

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number	UN1950
DOT	N/A
DOT	Consumer Commodity ORM-D
ADR	Aerosols, flammable
Transport hazard class(es):	1950 Aerosols
Class	2.1
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
ADR	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Packaging Group:	--
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

Toxic Substances Control Act (TSCA):

All ingredients for this product are found on the inventory list of substances.

Consumer Product Safety**Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

1333-86-4 Carbon black

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

CANADIAN ENVIRONMENTAL PROTECTION ACT:**WHMIS Symbols for Canada:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

A - Compressed gas

D2B - Toxic material causing other toxic effects

**EPA:**

67-64-1 Acetone

110-19-0 Isobutyl Acetate

108-10-1 methyl isobutyl ketone

USDA (United States Department of Agriculture):

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

16 Other information**Contact:**

Date of preparation / last revision

Regulatory Affairs

03/17/2017 / -